



SONIFEX

Redbox RB-PMX4

August 2008



www.sonifex.co.uk

t: +44 (0)1933 650 700

f: +44 (0)1933 650 726

sales@sonifex.co.uk

Redbox - Mixers & Source Selectors

RB-PMX4 10 Input, 4 Output Analogue Pre-set Mixer



// A high performance 10 mono input to 4 mono output pre-set mixer, designed for situations where a small mixer is needed for installations where it will be configured and then only altered occasionally, or never altered at all. **//**

The RB-PMX4 is a high performance 10 mono input to 4 mono output pre-set mixer. Each of the four outputs has a 10 way DIP switch associated with it to select which of the 10 inputs are routed to it. So, by altering the DIP switches, any of the input sources can be mixed to any of the outputs. The DIP switches are enclosed by a screw-on cover on the front panel so that the settings can not be accidentally changed for secure applications.

The RB-PMX4 has been designed for situations where a small mixer is needed for installations where it will be configured and then only altered occasionally, or never altered at all. Uses for this product are numerous including a four bus mini-mixer, a multiple clean-feed generator, a 4 zone mixer for pubs and clubs and a quad stereo to mono converter to name a few.

The XLR-3 inputs and outputs are electronically balanced and can be wired unbalanced. Each output is individually buffered so that a short circuit on one won't affect the others. Each input has its own gain control which is a pre-set potentiometer accessible through the front panel. This provides gain adjustment of -8dB to +18dB. This is useful for normalising consumer and professional signals to give outputs of -15dBu and 0dBu respectively.

Audio Specification For RB-PMX4

Input Impedance:	>20kΩ balanced bridging
Maximum Input Level:	+36dBu
Frequency Response:	20Hz to 20kHz ±0.1dB (600Ω load, @ 1kHz)
Common Mode Rejection:	>60dBu typically
Noise:	-86dBu RMS 22Hz-22kHz unity gain, ref +8dBu
Output Impedance:	<50Ω
Maximum Output Level:	+28dBu
Gain Range:	Adjustable -8dBu to +18dBu gain
Off-isolation/ Crosstalk:	>90dBu @ 1kHz
Distortion:	<0.01% @ 1kHz, 0dBu to +26dBu

Connections

Inputs:	10 x XLR 3 pin female (Balanced, can be unbalanced)
Outputs:	4 x XLR 3 pin male (Balanced, can be unbalanced)
Mains Input:	Filtered IEC, switchable 110-120V, or 220-240V, fused, 6W maximum
Fuse Rating:	Anti-surge fuse 100mA 20 x 5mm (230VAC) Anti-surge fuse 250mA 20 x 5mm (115VAC)

Equipment Type

RB-PMX4:	10 input, 4 output analogue pre-set Mixer
----------	---

Physical Specification

Dimensions (Raw):	48cm (W) x 10.8cm (D) x 4.2cm (H) (1U) 19" (W) x 4.3" (D) x 1.7" (H) (1U)
Dimensions (Boxed):	53cm (W) x 20.5cm (D) x 6cm (H) 21" (W) x 8" (D) x 2.4" (H)
Weight:	Nett: 1.5kg Gross: 2.2kg Nett: 3.3lbs Gross: 4.8lbs



SONIFEX

www.sonifex.co.uk

t:+44 (0)1933 650 700

f:+44 (0)1933 650 726

sales@sonifex.co.uk

61 Station Road
Irthlingborough
Northants NN9 5QE
United Kingdom

interstage

Phistersvej 31, 2900 Hellerup, Danmark
Telefon 3946 0000, fax 3946 0040
www.interstage.dk



- pro audio with a smile

