

**PRELIMINARY
INFORMATION**

302

Compact Production Mixer



GENERAL DESCRIPTION

The 302 from Sound Devices is a compact audio mixer designed for a wide range of audio-for-video applications. Its three full-featured microphone inputs, informative level metering, and flexible headphone monitoring provide complete control of audio sources. The 302 accepts a wide range of audio sources and provides phantom (48 or 12 V) or T-power — selectable per channel.

The 302 is the smallest and lightest audio mixer in its class. Powered from three-AA batteries, the 302 can operate for a full production day on internal cells (without phantom). Its durable mechanical construction and field-tested design will handle the most punishing field environments.

KEY FEATURES

- Three transformer-balanced mic or line level inputs
- Lundahl input transformers for excellent RF and signal handling
- Phantom (48 V or 12 V) or T-power selected per input
- Limiters on inputs and outputs (outputs software-controlled)
- MS stereo matrix on input channels 1 and 2
- Two-position high-pass filter, 80 Hz or 160 Hz @ 12 dB/octave
- Output level adjusted from line to mic level, controlled in setup menu
- 40-segment, sunlight viewable LED output meter, software controlled
- Slate microphone and tone oscillator
- Headphone monitoring of stereo program, mono program, return feed, PFL, or MS stereo
- Channel 4/5 option when more inputs are needed
- Software-controlled User Setups
- Easy access battery tube
- Powered from three-AA batteries or external 5 - 18 VDC

SOUND  DEVICES

Sound Devices, LLC
300 Wengel Drive
Reedsburg, WI 53959 USA
Ph: (608) 524-0625
Toll Free: (800) 505-0625
www.sounddevices.com

Features and specifications subject to change.

